

# AY-R6255

Illuminated CSN SELECT™ Smart Card Reader (Rev. B)



The CSN SELECT™ AY-R6255 is a unique illumination reader of multi-credential technology contactless smart card (13.56 MHz) readers for use in access control system solutions. The readers have the flexibility to read the Card Serial Number (CSN) from many smart card RFID standards, perfect for transitioning from one technology to another. The reader also supports access by an NFC compatible Android smartphone app\*. UV-resistant and with an IP65 rated sleek and modern design, the reader can be used comfortably in any installation environment whether indoors or outdoors.

## GENERAL DESCRIPTION

The standard AY-R6255 reader is configured to read the CSN of the most popular smart cards in the security industry, as well as NFC compatible Android smartphones, and outputs the Wiegand CSN data in Wiegand 26-Bit format. Four individual control lines provide green LED control, red LED control, and buzzer control inputs, as well as an output for the optical wall tamper detector. The reader can also communicate with host controllers that support the Open Standard Device Protocol (OSDP).

## MAIN FEATURES

- Read the CSN from the following smart cards:
  - ISO14443A - MIFARE® Ultralight® Nano / Ultralight EV1/ Ultralight C
  - - MIFARE Classic® / Classic EV1
  - - MIFARE Plus® S / SE / X / EV1
  - - MIFARE DESFire® EV1 / EV2
  - - NFC N-TAG / Card Emulation
  - ISO14443B - China National ID
  - ISO15693 - HID® iClass®, PicoPass™, iCode, LEGIC
  - ISO18092 - SONY® FeliCa® (Hong Kong Octopus)
- NFC Android Smartphone is supported with the Android App for HCE (Host Card Emulation)

- Multiple mounting options including micro-mullion, mullion, US gangbox and UK/Asia gangbox
- Supports a unique illumination system
- Selectable Wiegand output formats using the CS-HCT Hardware Configuration Tool for the DR-6255 application

## PROFESSIONAL GRADE FEATURES

- Sleek and modern design
- Customizable control and status lines available with CS-HCT Hardware Configuration Tool for the DR-6255 application
- Tri-colored LED operation
- Optical wall tamper detection
- IP65 rated and made of tough polycarbonate UV-resistant plastic
- Comes with mounting template and installation kit for easy installation

\*Please refer to NFC App data sheet for further information

# SPECIFICATIONS

## ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	8 ~ 16 VDC, from a regulated power supply
■ Standby Current @12V	160 mA
■ Maximum Current @12V	180 mA
■ Read Range*	5 cm (2 in.)
■ Tamper Output**	Open collector, active low, max. sink current 16 mA
■ Control Inputs**	Dry Contact, N.O.
■ Reader Data Output Formats	Selectable Wiegand output formats using the CS-HCT Hardware Configuration Tool for the DR-6255 application

## ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Weather-resistant, UV-resistant, meets IP65, epoxy-potted, suitable for indoor and outdoor use
■ Operating Temperature Range	-35°C to 66°C (-31°F to 150°F)
■ Operating Humidity Range	0% to 95% (non-condensing)

## PHYSICAL SPECIFICATIONS

■ Dimensions (H x W x D)	120.0 x 89.0 x 20 mm (4.7 x 3.5 x 0.8 in.)
■ Weight	208 g (7.3 oz)

## SYSTEM COMPONENTS

The AY-R6255 reader is compatible with a variety of Rosslare controllers, as well as with many third-party access control systems supporting Wiegand

## PRODUCT WARRANTY

5-Year Limited Product Warranty

- \* Measured using a Rosslare MIFARE Classic EV1 (ISO Card). Read range with other credential technologies may vary. Range also depends on electrical environment and proximity to metal.
- \*\* Control lines are factory programmable and can be custom configured upon request.
- \*\*\* Standard readers output the Wiegand CSN data in Wiegand 26-Bit format by default. Other formats such as Clock & Data and Wiegand 32-, 32R-, 34-, 40-, 56-, and 64-Bit can be selected using the CS-HCT Hardware Configuration Tool for the DR-6255 application or by locally selecting via keypad programming. Custom formats are available upon request.

## ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

[www.rosslaresecurity.com](http://www.rosslaresecurity.com)

MIFARE, Ultralight, Classic, Plus, DESFire and iCode are registered trademarks of NXP B. V.  
 iClass is a registered trademark of HID  
 FeliCa is a registered trademark of Sony  
 All data contained herein subject to change without notice

5505-3013101-00  
 Copyright © Rosslare



**ROSSLARE**  
 SECURITY PRODUCTS  
 Experience the Difference